



SYSTEMC™

TLM 2.0 Loosely Timed (LT) System Example - Temporal Decoupled


Jack Donovan, Anna Keist, Charles Wilson
ESLX, Inc.
June 2008

AT System Example - Annotated Timing

- The Goal is to Illustrate:
 - Application of TLM 2.0 in a real system
 - Annotated non-blocking (NB) option of the non-blocking style
 - ◆ NB annotated timing has been referred to as "1 phase"
 - ◆ Simplest version of non-blocking/AT
- Possible Applications:
 - Architectural exploration
 - Early software development



Example Block Diagram



↔ TLM 2 GP



How to run this example (Linux)

- Set `SYSTEMC_HOME`
- `cd examples/tlm/lt_temporal_decouple/build-unix`
- `make clean`
- `make`
- `make run`



How to run this example (MSVC)

- Open a explorer window on `examples/tlm/l1t_temporal_decouple/build-windows`
- Launch `l1t.sln`
- Select ‘Property Manager’ from the ‘View’ menu
- Under ‘`l1t_temporal_decouple > Debug | Win32`’ select ‘`systemc`’
- Select ‘Properties’ from the ‘View’ menu
- Select ‘User Macros’ under ‘Common Properties’
- Update the ‘`SYSTEMC`’ entry and apply
- Build and run



Expected Output (expected.log)

....

Info: It_initiator.cpp: 0 s - initiator_thread
Initiator: 102 b_transport(GP, 0 s)

Info: memory.cpp: 0 s - print
ID: 201 COMMAND: WRITE Length: 04
Addr: 0x0000000000000000 Data: 0x00000000

Info: It_synch_target.cpp: 0 s - custom_b_transport
Target: 201 Forcing a synch in a temporal decoupled initiator with wait(80 ns),


Info: It_synch_target.cpp: 80 ns - custom_b_transport
Target: 201 return from wait will return a delay of 0 s

....


Info: It_initiator.cpp: 80 ns - initiator_thread
Initiator: 102 b_transport returned delay = 0 s




Initiator Module



TLM Interface Module



Target Module (`lt_target` or `lt_synch_target`)



Router Component

Router Model (`simpleBusLT<2, 2>`)

